

Solid Glazing Products **Installation Guide**





Virtually Unbreakable Glazing Sheets

Axgard® glazing sheets are specified where a high degree of strength is required to protect against impact and provide a safe glazing solution in the place of glass. The Axgard® material is extruded from a polymer resin which is approximately 200 times stronger than glass of the same thickness and is therefore classed as virtually unbreakable.

Unlike many other plastic glazing options, Axgard® sheets are manufactured with an additional layer which protects the material from degradation due to the effects of ultra violet light.


- How 2 Cut Solid Glazing Sheets Video
- How 2 Drill Solid Glazing Sheets Video



Axgard® Glazing Bar Systems



- √ Fully aluminium
- ✓ Ideal for timber and metal structures
- ✓ Suits Axiome®, Axgard® and glass of any thickness
- √ Concealed fixings
- √ 20 years life expectancy



- √ Fully aluminium
- √ Self-supporting
- ✓ Suits Axiome®, Axgard® and glass of any thickness
- ✓ Immense spanning capabilities
- √ 20 years life expectancy



- √ Fully aluminium
- √ Secondary Glazing for Solution
- ✓ Suitable for 2mm and 3mm Axgard[®] sheets
- ✓ Quick snap fix fittings
- √ 20 years life expectancy



Alukap®-XR Aluminium Glazing Bar System





Alukap®-SS Self Supporting Glazing Bar System





Sekosnap® Secondary Glazing System

A typical Sekosnap® Secondary Glazing set-up showing the components for a successful installation. Please note: this system is not for roofing applications.



Need Guttering for Your Project?

- √ 50kg/m Weight Tested
- √ 60 Year Est Lifespan
- ✓ Hidden Brackets & Unions
- ✓ Sustainable & Recyclable





Click To View The Aluflow® Aluminium Guttering Range

WARNING: REGISTERED DESIGNS & PATENTS

The IP of the designs in this brochure are protected by internationally registered design rights. Many products are also protected with active or pending Patents. Clear Amber will not hesitate to take appropriate legal action if its rights in this respect are infringed.

Disclaimer

Once Axgard® polycarbonate sheets has left our warehouse, we cannot control transportation, storage, installation or handling, nor can we influence installation conditions, Clear Amber Group cannot be held responsible in any

way for condensation issues or other installation problems that may arise, or any associated remedial work. All advice is offered in good faith based on our experience. Installers should apply best practices before and during installation.

© Copyright – Clear Amber Group Ltd – February 2024. No part of this publication may be copied, reproduced, scanned, or stored in any electronic database, whether in whole or in part, in any form or by any means, without permission in writing from Clear Amber. Clear Amber will not hesitate to take appropriate legal action if its rights in this respect are infringed.

Inasmuch as Clear Amber have no control over the circumstances in which our material may be used, or site specific parameters, we cannot guarantee that any particular results will be achieved. Users should carry out their own tests to determine the suitability of the material for their application.

